456036

Material Safety Data Sheet

MSDS No. 0022 Rev. 5

0420, 0422, 0424, 0425, 0428, 0438 Pre-mixed Tile Grout - White

Emergency Phone No. 800-535-5053 - INFOTRAC

	SECTION 1 – P	RODUCT NAME &	MANUFACTURER I	INFORM	ATION		
PRODUCT NAME	Pre-mixed Tile Gro	ut - White					
MANUFACTURER'S N TELEPHONE NUMBER							
STREET ADDRESS	4175 Webb Street						
CITY / STATE / ZIP	Pryor, Oklahoma 7	4361					
SECTION 2 – COMPOSITION / HAZARDOUS INGREDIENTS					TLV	PEL	UNITS
PRODUCT CONSISTS	OF:						
Calcium Carbo	onate ** (1317-65-3)			< 70	10	15	mg/m3
Acrylic Emuls	ion Blend (mixture)			< 25	NE	NE	
Titanium Dioxide ** (13463-67-7)					10	10	mg/m3
Petroleum Distillate/Mineral Spirits (64742-48-9)					100	100	ppm
Ammonium H	lydroxide (7664-41-7)			< 0.15	25	50	ppm
Non-hazardou *Unlisted ingr 1910.1200). * Calculated VC	<15	NA	NA				
	S	ECTION 3 – HAZAR	RDS IDENTIFICATIO	DN			
PRIMARY ROUTE(S) OF ENTRY	Skin Contact	Skin Absorption	Eye Contact	Inhalation Ingestion			
EMERGENCY OVERVIEW	White, slightly textured paste	. Harmful if swallowed.					
EFFECTS OF Eye: Causes eye irritation. Skin: Causes skin irritation. Inhalation: Harmful if inhaled. May cause nose & throat irritation. Ingestion: Harmful if swallowed. Chronic Hazards: Formaldehyde vapor (trace residual Formaldehyde present in base acrylic emulsion) is a known animal carcinogen (IARC & NTP) & is considered possibly carcinogenic to humans by inhalation.							
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	None known.						
SECTION 4 – FIRST AID MEASURES							
SKIN CONTACT	SKIN CONTACT Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.						
EYE CONTACT	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.						
INHALATION Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.							
INGESTION DO NOT INDUCE VOMITING. Get immediate medical attention.							

SECTION 5 – FIRE FIGHTING MEASURES									
FLAMMABLE Yes No									
EXTINGUISHING		xide, Dry Chemical, Foam, Water Fog	y 2						
MEDIA FLASHPOINT (°F) &	& >200F	(Seta Closed Cup)	UPPER EXPLOS						
METHOD LOWER EXPLOSIV	VE LIMIT NE		(% BY VOLUME AUTOIGNITION	NE					
(% BY VOLUME) UNUSUAL FIRE & I	EXPLOSION Non	e known.	TEMPERTURE (°F)					
HAZARDS SPECIAL Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces. PROCEDURES cool exposed surfaces.									
		SECTION 6 – ACCI	DENTAL RELEA	ASE MEASURES					
PROCEDURES	Were more a motority any impact (Castion 2). Use charge antipical an ensure and independent of allogs in compared container								
			- HANDLING & S						
HANDLING PROCE EQUIPMENT	HANDLING PROCEDURES & EQUIPMENT Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing.								
STORAGE REQUIR	REMENTS Close c	ontainer after each use. Store containe away from caustics & oxidizers.	ers away from excessive heat	& freezing. Do not store @ temperatures above 120F. Store					
	SEC	TION 8 – EXPOSURE	CONTROL / PER	SONAL PROTECTION					
RESPIRATORY In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator w/ organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits.									
EYEWEAR	EYEWEAR Goggles or safety glasses w/ side shields.								
CLOTHING / GLOVES	Rubber gloves. Oth	her protective equipment not required u	under normal use.						
HYGENIC PRACTICES									
		SECTION 9 – PHYSIC	AL AND CHEMI	CAL PROPERTIES					
PHYSICAL STATE		Paste	ODOR & APPEARANCE	Mild acrylic/ammonia odor, v slightly textured white paste					
SPECIFIC GRAVITY	Y	Approximately 1.50 to 2.0	VAPOR DENSITY (AIR=1)	>1					
EVAPORATION RA	ATE	NE	BOILING RANGE (°F)	NE					
рН		Approximately 7 to 10	SOLUBILITY IN WATER	Slightly soluble prior to full cure					
VAPOR PRESSURE Hg)	E (MM	NE	%/WT VOLATILE (TNV)	< 25					
SECTION 10 – STABILITY AND REACTIVITY									
STABILITY Xes No Stable under normal conditions.									
INCOMPATABILITY Xes No Incompatible w/ strong bases & oxidizing agents.									
CONDITIONS TO AVOID									
HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS									

S	ECTION 11 - TOXICOLOGICAL IN	FORMATION / CARCINOGENICITY						
ACGIH								
	Small amount of Silica, crystalline present in Calcium Carbonate & trace residual Formaldehyde present in base emulsion are suspected human carcinogens.							
OSHA	Trace residual Formaldehyde present in base emulsion viewed as a possible cancer hazard.							
IARC	Trace residual Formaldehyde: Potential human carcinogen.							
NTP	Silica, crystalline, present in small amount in Calcium Carbonate Filler: Known carcinogen. Trace residual Formaldehyde: Anticipated carcinogen.							
DATA WITH POSSIBLE RELEVANCE TO HUMANS								
	SECTION 12 – ECOLO	GICAL INFORMATION						
AQUATIC TOXICITY								
	SECTION 13 – DISPOS	AL CONSIDERATIONS						
WASTE DISPOSAL	Dispose of material in accordance w/ Federal, State & Loc	al regulations.						
EPA WASTE CODE IF DISCARDED (40CFR Sec.261)	None.							
	SECTION 14 – TRANS	PORT INFORMATION						
SPECIAL SHIPPING INFORMATION	Product not regulated by DOT.							
	SECTION 15 – REGULA	TORY INFORMATION						
CERCLA - SARA Imm HAZARD CATEGORY	nediate health hazard; chronic health hazard.	U.S. STATE See Section 16. REGS						
SARA 313 Nor	ne.	TSCA All ingredients either on TSCA Inventory or exempt.						
SEC	CTION 16 – OTHER INFORMATION	V / SPECIAL PRECAUTIONS / LEGEND						
Dioxide (13463-67-7). Pe toxicity &/or reproductive Right to Know List, Minn	ennsylvania Right-to-Know (Non-Haz @ >3%): Water (7732- e toxicity: Silica, crystalline & Formaldehyde. <u>HMIS Ratings</u> : nesota Hazardous Substance List, New Jersey Right to Know I t contains chemicals known to the State of California to cause	Emulsion (mixture), Water (7732-18-5), Petroleum Distillate (64742-48-9), Titanium 8-5). <u>Ingredients Known to State of California to cause cancer &/or developmental</u> Health: 1, Flammability: 0, Reactivity: 0. Titanium Dioxide added to Massachusetts ist, Pennsylvania Right to Know List & Rhode Island Hazardous Substance List. cancer, birth defects or other reproductive harm. INTERNATIONAL EMERGENCY						
Threshold Limit Value, Hygienists, SARA – Sup	STEL – Short Term Exposure Limit, MSDS – Material S perfund Amendments & Reauthorization Act of 1986, OSI TP – National Toxicology Program, CEIL – Ceiling Expo	Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – fety Data Sheet, ACGIH – American Conference of Governmental Industrial IA – Occupational Safety & Health Administration, HMIS – Hazardous Materials sure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry						
Reviewed By: <u>Larry G</u> NA	. Brandon VP Technology & Ger ME TITLE	neral Manager March 19, 2012 DATE						
		ntific data. New information may be developed from time to time which may render the lity of this information to the user's intended purpose or for the consequences of its use						

3